



Networking Options for ThinkSystem Servers

Reference Information

Ethernet Network Adapters

ThinkSystem Ethernet adapters provide industry latest networking solutions to address Ethernet, Converged and Virtualized data center networking requirements.

- [100 Gb Ethernet Adapters](#)
- [40 Gb Ethernet Adapters](#)
- [25 Gb Ethernet Adapters](#)
- [10 Gb Ethernet RJ45 Adapters](#)
- [10 Gb Ethernet SFP+ Adapters](#)
- [Gigabit Ethernet Adapters](#)

100 Gb Ethernet Adapters

100 Gb Ethernet connections for the ultimate in network I/O performance.

Mellanox ConnectX-4 100GbE/EDR IB QSFP28 VPI Adapters

ConnectX-4 from Mellanox is a family of high-performance and low-latency adapters. The 100GbE/EDR VPI adapters, available as either a 1-port or a 2-port adapter, supports 100 Gb Ethernet connections for the ultimate in network I/O performance.

Learn more:

- [Product guide](#)



40 Gb Ethernet Adapters

40 Gb Ethernet delivers improved application performance through higher bandwidth, lower latency enabling increased VM density per host.

Mellanox ConnectX-4 Lx 1x40GbE QSFP+ Adapter

ConnectX-4 from Mellanox is a family of high-performance and low-latency adapters. The ConnectX-4 Lx 1x40GbE supports a single 40 Gb Ethernet port for high-speed networking with a PCIe x8 host interface.

Learn more:

- [Product guide](#)



Mellanox ConnectX-4 FDR 2-Port QSFP VPI Adapter

Two-port ConnectX-4 VPI adapter supports either 40 Gb Ethernet or FDR InfiniBand. Ideal for customers need to maximize high-speed networking connectivity when only a PCIe x8 host interface is available.

Learn more:

- [Product guide](#)



Mellanox ConnectX-3 Pro ML2 FDR 2-Port QSFP VPI Adapter

ConnectX-3 adapter with two QSFP ports supporting 40 Gb Ethernet or InfiniBand FDR speeds. Supported in servers with an ML2 adapter slot.

Learn more:

- [Product guide](#)



Mellanox ConnectX-3 Mezz 40Gb 2-Port Ethernet Adapter

Provides high-speed connectivity with ThinkSystem servers for the Flex System ecosystem. Works in conjunction with the EN6131 40Gb Ethernet Switch for Flex System.

Learn more:

- [Product guide](#)



25 Gb Ethernet Adapters

25 Gb significantly lowers cost per Gb and enables server future proofing. Lenovo's 25 Gb adapters can be installed now and operated at 10 Gb utilizing existing switches and cabling.

Mellanox ConnectX-4 Lx 25GbE SFP28 Adapters

ConnectX-4 from Mellanox is a family of high-performance and low-latency adapters. The 25 GbE adapters are available as either 1-port or 2-port. Adapters are available as either PCIe or ML2 form factor.

Learn more:

- [Product guide](#)



Broadcom NX-E PCIe 25Gb 1-Port SFP28 Ethernet Adapter

Broadcom's NX-E adapters offer TruFlow intelligent flow processing and support advanced networking technologies including RoCE, SDN, NFV and virtualization. The 25Gb adapter is offered as a 1-port PCIe adapter.

Learn more:

- [Product guide](#)



Intel XXV710-DA2 PCIe 25Gb 2-Port SFP28 Ethernet Adapter

25 Gb Ethernet adapter with excellent small packet performance, offering virtualization features with support for GENEVE, VXLAN, NVGRE offloads, DPDK, SR-IOV, and VMDq protocols.

Learn more:

- [Product guide](#)



10 Gb Ethernet RJ45 Adapters

10GBASE-T adapters with CAT-6a cabling are a low-cost way to implement 10 Gb Ethernet.

Broadcom NX-E 10GBASE-T Adapters

Dual-port 10GBASE-T adapters featuring advanced flow processing and virtualization support while providing a low-cost solution for 10 Gb Ethernet using copper cabling. Available in either ML2 or PCIe low-profile form factor for ThinkSystem servers.

Learn more:

- [Product guide](#)



Intel X550 10 Gb Ethernet 10GBASE-T Adapters

A cost-effective and power-efficient 10 GbE performance adapter suitable for all data center applications. Support for standard CAT 6a cabling with RJ45 connectors, the X550 offers a low barrier of entry to 10 Gb Ethernet networking. Available as a 1-port or 2-port adapter.

Learn more:

- [Product guide](#)



Intel X722 Integrated 10 GbE Controller with 10 Gb LOM

The Intel Ethernet Connection X722 is a network controller embedded into ThinkSystem servers. 10 Gb LOM adapters with 10GBASE-T connections enable support for two or four 10 GbE connections using low-cost RJ45 twisted-pair cabling.

Learn more:

- [Product guide](#)



10 Gb Ethernet SFP+ Adapters

10 GbE SFP+ adapters offer the flexibility of using either short-run copper cables or SFP+ transceivers and lightweight long-run fibre optic cabling.

Emulex OCe14100B VFA5.2 Adapters

The Emulex Virtual Fabric Adapter 5.2 adapter family of PCIe and ML2 adapters support NIC partitioning with 16 virtual NIC (vNIC) functions per adapter. They support datacenter functions including VxLAN/NVGRE and RoCE v2. Advanced adapters also include FCoE and iSCSI support.

Learn more:

- [Product guide](#)



Emulex CN4052S and CN4054S 10Gb VFA5.2 Adapters for Flex System

High performance family of 10 GbE adapters for SN550 and SN850 compute nodes supporting NIC partitioning with 16 vNICs per adapter and datacenter functions including VxLAN/NVGRE and RoCE v2. Advanced adapters also include FCoE and iSCSI support.

Learn more:

- [Product guide](#)



Intel X710 10 GbE SFP+ Network Adapters

Ideal for server and network virtualization, small packet performance, and low power requirements. Available in either PCIe or ML2 form factor for ThinkSystem servers.

Learn more:

- [Product guide](#)



Intel X722 Integrated 10 GbE Controller with 10 Gb LOM

The Intel Ethernet Connection X722 is a network controller embedded into ThinkSystem servers. 10 Gb LOM adapters with SFP+ cages for either optical transceivers or direct-attach copper (DAC) cable connections. Available in two or four port configurations.

Learn more:

- [Product guide](#)



Gigabit Ethernet Adapters

1 Gb adapters offer low cost, low power solutions enabling server virtualization and reduced CPU overhead with adapter offloads.

Broadcom NetXtreme Gigabit Ethernet Adapters

2-port and 4-port Gigabit Ethernet adapters with RJ45 connectors supporting CAT5 cabling for low-cost and flexible networking requirements.

Learn more:

- [Product guide](#)



Intel I350 Gigabit Ethernet Adapters

Available in either 1-port fiber configuration or 2-port or 4-port copper configurations, these adapters offer excellent price/performance, enhanced power-savings, and market-leading I/O virtualization technologies that includes SRIOV and VMDq.

Learn more:

- [Product guide](#)



Intel X722 Integrated 10 GbE Controller with Gigabit LOM

The Intel Ethernet Connection X722 is a network controller embedded into ThinkSystem servers. 1 Gb LOM adapters with RJ45 connections enable support for two or four Gigabit Ethernet network links.

Learn more:

- [Product guide](#)



Fibre Channel Adapters

Connecting Lenovo Servers to Storage Area Networks. High performance single and dual port Fiber Channel adapters provide performance, power efficiency, reliability and investment protection for connectivity to data center storage.

- [32 Gb Fibre Channel HBAs](#)
- [16 Gb Fibre Channel HBAs](#)

32 Gb Fibre Channel HBAs

32 Gb FC host bus adapter are Generation 6 (Gen 6) Fibre Channel offerings that provide the ultimate in Storage Area Network connectivity.

Emulex 32Gb Fibre Channel Adapters

Emulex 32 Gb 1-port and 2-port FC HBAs for ThinkSystem servers are an ideal solution when requiring high-speed data transfer in storage connectivity for virtualized environments, data backup, and mission-critical applications.

Learn more:

- [Product Guide](#)



QLogic 32Gb Fibre Channel Adapters

1-port and 2-port adapters based on Cavium technology offering industry leading native FC performance with extremely low CPU usage with full hardware offloads.

Learn more:

- [Product Guide](#)



16 Gb Fibre Channel HBAs

Fibre Channel HBAs deliver performance, operational agility, & maximum power of cloud virtualization.

Emulex 16 Gb Gen 6 Fibre Channel Host Bus Adapters

1-port and 2-port adapters with an advanced ASIC that can achieve 1.6M IOPS on a single port. Based on Emulex's new Dynamic Multicore architecture, which for the 2-port adapter, dynamically scales HBA resources to one port if the other port is idle.

Learn more:

- [Product guide](#)



QLogic Enhanced Gen 5 16 Gb Fibre Channel HBAs

1-port and 2-port adapters based on QLogic StorFusion architecture to delivers ultimate reliability to meet the needs of mission-critical enterprise applications. Consumes less power and fewer CPU cycles, all while maintaining peak performance.

Learn more:

- [Product guide](#)



Emulex LPm16002B-L Mezz 16Gb Fibre Channel Adapters for Flex System

1-port and 2-port Flex System mezz cards based on the proven Emulex XE201 design. Deliver 6x the IOPS, improve response times by up to 75%, and deliver double the throughput speeds compared to previous-generation 8 Gb adapters.

Learn more:

- [Product guide](#)



QLogic QML2692 16 Gb Enhanced Gen 5 Fibre Channel Adapter for Flex System

2-port mezz card for Flex System based on the advanced Cavium StorFusion architecture and ASIC. Delivers higher IOPS and performance with lower power consumption compared to previous generation.

Learn more:

- [Product guide](#)



InfiniBand and Omni-Path Adapters

InfiniBand and Omni-Path Architecture (OPA) adapters are the gateway to high-performance low-latency networking, ideal for clusters and time-sensitive applications.

- [InfiniBand Adapters](#)
- [Omni-Path Adapters](#)

InfiniBand Adapters

InfiniBand adapters solve HPC cluster networking challenges by delivering high bandwidth, low latency, and CPU offloads to get the highest server efficiency and application productivity at scale.

Mellanox ConnectX-4 100GbE/EDR IB QSFP28 VPI Adapters

1-port or 2-port adapters that offer InfiniBand EDR speeds (25.8 Gb/s per lane) to enable high performance networking, clustering, or storage to operate seamlessly over any converged network leveraging a consolidated software stack.

Learn more:

- [Product guide](#)



Mellanox ConnectX-4 FDR 2-Port QSFP VPI Adapter

2-port adapter supporting InfiniBand FDR speeds (14 Gb/s per lane). Ideal for customers needing high-speed cluster interconnects using a PCIe x8 host interface.

Learn more:

- [Product guide](#)



Mellanox ConnectX-3 Pro ML2 FDR 2-Port QSFP VPI Adapter

Two QSFP ports supporting InfiniBand FDR speeds (14 Gb/s per lane) or 40 Gb Ethernet. Supported in servers with an ML2 adapter slot.

Learn more:

- [Product guide](#)



Mellanox ConnectX-3 Mezz FDR 2-Port InfiniBand Adapter for Flex System

Delivers low latency and high bandwidth for performance-driven server clustering applications on ThinkSystem servers in a Flex System ecosystem. Operates at InfiniBand FDR speeds (56 Gbps or 14 Gbps per lane)

Learn more:

- [Product guide](#)



Omni-Path Adapters

Omni-Path Architecture is a new networking topology that was designed specifically to scale cost-effectively from entry level HPC clusters to larger clusters with 10,000 nodes or more.

Intel Omni-Path Architecture OPA 100 Series Host Fabric Adapters

Enable high-performance connectivity between servers in a cluster. Available as either a PCIe 3.0 x16 adapter supporting bandwidths up to 100 Mb/s, or a PCIe 3.0 x8 adapter supporting up to 58 Mb/s.

Learn more:

- [Product guide](#)



Related product families

Product families related to this document are the following:

- [Ethernet Adapters](#)
- [InfiniBand & Omni-Path Adapters](#)
- [Host Bus Adapters](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
1009 Think Place - Building One
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2018. All rights reserved.

This document, LP0765, was created or updated on November 21, 2017.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<http://lenovopress.com/LP0765>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <http://lenovopress.com/LP0765>.

Trademarks

Lenovo, the Lenovo logo, and For Those Who Do are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <http://www3.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Flex System

Lenovo®

ThinkSystem

vNIC

The following terms are trademarks of other companies:

Intel® is a trademark or registered trademark of Intel Corporation or its subsidiaries in the United States and other countries.

Other company, product, or service names may be trademarks or service marks of others.