

Product	Primary Port	Uplink	Temp Range ¹	PoE Power Budget	PoE Sourcing Ports	PoE Sourcing Ports at Full Load			
						802.3bt Type 4 PoE++ (90W)	802.3bt Type 3 PoE++ (60W)	802.3at Type 2 PoE+ (30W)	802.3af/at Type 1 PoE (15.4W)
CHASSIS-BASED SWITCHES — LAYER 3									
SBx8112	Up to 400 modular	-	0°C to 40°C	1200W or 2400W	240	-	-	80	155
SBx8106	Up to 200 modular	-	0°C to 40°C	1200W or 2400W	120	-	-	80	120
10/100/1000 MANAGED SWITCHES — STACKABLE LAYER 3									
x930-52GPX	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	380W - 1440W or 380W - 740W Redundant	48	-	-	48	48
x930-28GPX	20 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	380W - 1440W or 380W - 740W Redundant	24	-	-	24	24
x550-18XSPQm	8 x 1/2.5/5/10G Ethernet 8 x 10G Ethernet	2 x 40G Ethernet	0°C to 45°C	240W	8	-	-	8	8
x530-52GPXm	40 x Gigabit Ethernet 8 x 1/2.5/5 Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 50°C	740W	48	-	-	24	48
x530-28GPXm	20 x Gigabit Ethernet 4 x 1/2.5/5 Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 50°C	740W	24	-	-	24	24
x530DP-28GHXm ²	20 x Gigabit Ethernet 4 x 1/2.5/5 Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 50°C	1440W	24	-	24	24	24
x530L-52GPX	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 50°C	740W	48	-	-	24	48
x530L-28GPX ²	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 50°C	740W	24	-	-	24	24
x530L-10GHXm ²	8 x 1/2.5/5 Gigabit Ethernet	2 x 10 Gigabit Ethernet	0°C to 50°C	500W	8	5	8	8	8
x510-52GPX	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	370W	48	-	-	12	24
x510-28GPX	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	370W	24	-	-	12	24
x510L-52GP	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	185W	48	-	-	6	12
x510L-28GP	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	185W	24	-	-	6	12
10/100/1000 MANAGED SWITCHES — LAYER 3									
IE340-20GP	16 x Gigabit Ethernet	4 x Gigabit Ethernet	-40°C to +75°C	240W	16	-	-	8	16
IE340L-18GP	16 x Gigabit Ethernet	2 x Gigabit Ethernet	-40°C to +65°C	240W	16	-	-	8	16

¹ Stated temperature range is for full PoE load. See specific product datasheet for any wider operating temperature information

² Coming soon

Product	Primary Port	Uplink	Temp Range ¹	PoE Power Budget	PoE Sourcing Ports	PoE Sourcing Ports at Full Load			
						802.3bt Type 4 PoE++ (90W)	802.3bt Type 3 PoE++ (60W)	802.3at Type 2 PoE+ (30W)	802.3af/at Type 1 PoE (15.4W)
10/100/1000 MANAGED SWITCHES — LAYER 3									
IE340-12GP	8 x Gigabit Ethernet	4 x Gigabit Ethernet	-40°C to 75°C	240W	8	-	-	8	8
IE300-12GP	8 x Gigabit Ethernet	4 x Gigabit Ethernet	-40°C to 75°C	240W	8	-	4 (Hi-PoE) ³	8	8
x320-10GH	8 x Gigabit Ethernet	2 x Gigabit Ethernet	-10°C to 55°C	720W	8	8	8	8	8
x320-11GPT ²	9 x Gigabit Ethernet	2 x Gigabit Ethernet	-10°C to 55°C	46W	8	-	-	1	3
GS980EM/10H	8 x Gigabit Ethernet	2 x Gigabit Ethernet	-10°C to 55°C	720W	8	8	8	8	8
xGS980EM/11PT ²	9 x Gigabit Ethernet	2 x Gigabit Ethernet	-10°C to 55°C	46W	8	-	-	1	3
10/100 MANAGED SWITCHES — STACKABLE LAYER 3									
x310-50FP	48 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 50°C	370W	48	-	-	12	24
x310-26FP	24 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 50°C	370W	24	-	-	12	24
10/100/1000 MANAGED SWITCHES — STACKABLE LAYER 2									
IX5-28GPX	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 50°C	370W or 720W	24	-	-	24	24
GS948MPX	48 x Gigabit Ethernet	2 x 10 Gigabit Ethernet	0°C to 50°C	370W	48	-	-	12	24
GS924MPX	24 x Gigabit Ethernet	2 x 10 Gigabit Ethernet	0°C to 50°C	370W	24	-	-	12	24
10/100/1000 MANAGED SWITCHES — LAYER 2									
x230-28GP	24 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 50°C	370W	24	-	-	12	24
x230-18GP	16 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 50°C	247W	16	-	-	8	16
x230-10GP	8 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 50°C	124W	8	-	-	4	8
x220-52GP	48 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 50°C	740W	48	-	-	24	48
GS980M/52PS	48 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 50°C	740W	48	-	-	24	48
GS970M/28PS	24 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 50°C	370W	24	-	-	12	24
GS970M/18PS	16 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 50°C	247W	16	-	-	8	16
GS970M/10PS	8 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 50°C	124W	8	-	-	4	8
IE210L-18GP	16 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 65°C	247W	16	-	-	8	16
IE210L-10GP	8 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 65°C	124W	8	-	-	4	8
IE200-6GP	4 x Gigabit Ethernet	2 x Gigabit Ethernet	-40°C to 75°C	120W	4	-	-	4	4

¹ Stated temperature range is for full PoE load. See specific product datasheet for any wider operating temperature information

² Coming soon

³ Hi-PoE is a proprietary implementation of 60W 4-pair PoE

Product	Primary Port	Uplink	Temp Range ¹	PoE Power Budget	PoE Sourcing Ports	PoE Sourcing Ports at Full Load			
						802.3bt Type 4 PoE++ (90W)	802.3bt Type 3 PoE++ (60W)	802.3at Type 2 PoE+ (30W)	802.3af/at Type 1 PoE (15.4W)
10/100/1000 MANAGED SWITCHES — LAYER 2									
IS230-10GP	8 x Gigabit Ethernet	2 x Gigabit Ethernet	-40°C to 75°C	120W	8	-	-	4	8
FS980M/52PS	48 x Fast Ethernet	4 x Gigabit Ethernet	0°C to 50°C	375W	48	-	-	12	24
FS980M/28PS	24 x Fast Ethernet	4 x Gigabit Ethernet	0°C to 50°C	375W	24	-	-	12	24
10/100 MANAGED SWITCHES — LAYER 2									
FS980M/18PS	16 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 50°C	250W	16	-	-	8	16
FS980M/9PS	8 x Fast Ethernet	1 x Gigabit Ethernet	0°C to 50°C	150W	8	-	-	4	8
IE200-6FP	4 x Fast Ethernet	2 x Gigabit Ethernet	-40°C to 75°C	120W	4	-	-	4	4
IFS802SP/POE	8 x Fast Ethernet	2 x Gigabit Ethernet	-40°C to +75°C	123W	8	-	-	-	8
10/100/1000 UNMANAGED AND WEBSMART SWITCHES									
GS950/48PS	48 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 40°C	370W	24	-	-	12	24
GS950/28PS	24 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 40°C	185W	24	-	-	4	12
GS950/16PS	14 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 40°C	185W	16	-	-	6	12
GS950/10PS	8 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 40°C	75W	8	-	-	2	4
GS920/8PS	8 x Gigabit Ethernet	-	0°C to 50°C	62W	8	-	-	2	4
IS130-6GP	5 x Gigabit Ethernet	1 x Gigabit Ethernet	-40°C to 75°C	90W	4	-	-	3	4
10/100 UNMANAGED AND WEBSMART SWITCHES									
FS750/28PS	24 x Fast Ethernet	4 x Gigabit Ethernet	0°C to 40°C	193W	24	-	-	4	12
FS708/POE	8 x Fast Ethernet	-	0°C to 40°C	65W	4	-	-	-	4

¹ Stated temperature range is for full PoE load. See specific product datasheet for any wider operating temperature information

Media converters, network cards, splitters and injectors are also available from Allied Telesis. Please contact your local sales office for more information or visit our website.

UK Sales | Phone: +44 1793 501408 | Email: UK_Sales@Alliedtelesis.com | Web: www.alliedtelesis.com



NETWORK SMARTER

North America Headquarters | 1980 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

EMEA & CSA Operations | Incheonweg 7 | 1437 EK Rozenburg | The Netherlands | T: +31 20 7950020 | F: +31 20 7950021

alliedtelesis.com

© 2020 Allied Telesis, Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners[®]

C618-3410015 RevU